

US008003073B2

(12) United States Patent

Pez et al.

(10) Patent No.: US 8,0 (45) Date of Patent: Au

US 8,003,073 B2 Aug. 23, 2011

(54) AUTOTHERMAL HYDROGEN STORAGE AND DELIVERY SYSTEMS

(75) Inventors: **Guido Peter Pez**, Allentown, PA (US);

Alan Charles Cooper, Macungie, PA (US); Aaron Raymond Scott,

Allentown, PA (US)

(73) Assignee: Air Products and Chemicals, Inc.,

Allentown, PA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 12/103,205

(22) Filed: **Apr. 15, 2008**

(65) **Prior Publication Data**

US 2008/0260630 A1 Oct. 23, 2008

Related U.S. Application Data

- (60) Provisional application No. 60/911,988, filed on Apr. 16, 2007.
- (51) **Int. Cl. C01B 3/26** (2006.01) **C01B 6/24** (2006.01)
- (52) **U.S. Cl.** 423/651; 423/644

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,483,210 A	12/1969	Rosenblatt et al.
3,843,216 A	10/1974	Campbell
4,042,621 A	8/1977	Sauer
4,359,404 A	11/1982	Grey et al.
4,560,816 A *	12/1985	Davis, Jr 585/266

4,567,033	\mathbf{A}	1/1986	Kesten	
5,958,821	A *	9/1999	Ishii et al 502/167	
6,455,830	B1	9/2002	Whalen et al.	
7,101,530	B2	9/2006	Pez et al.	
7,108,933	B2	9/2006	Gelsey	
7,294,420	B2 *	11/2007	Hodges 429/17	
7,351,395	В1	4/2008	Pez et al.	
2003/0008187	A1*	1/2003	Higashiyama et al 429/19	
2003/0046867	A1*	3/2003	Woods et al 48/127.9	
2003/0092877	A1	5/2003	Amendola et al.	
(Continued)				

FOREIGN PATENT DOCUMENTS

EP 0779264 6/1997 (Continued)

OTHER PUBLICATIONS

John H. Sinfelt "The turnover frequency of methylcyclohexane dehydrogenation to toluene on a Pt reforming catalyst" Journal of molecular catalysis. Feb. 11, 2000.*

(Continued)

Primary Examiner — Jessica L Ward

Assistant Examiner — Alexander Polyansky
(74) Attorney, Agent, or Firm — Michael K. Boyer

(57) ABSTRACT

Processes are provided for the storage and release of hydrogen by means of dehydrogenation of hydrogen carrier compositions where at least part of the heat of dehydrogenation is provided by a hydrogen-reversible selective oxidation of the carrier. Autothermal generation of hydrogen is achieved wherein sufficient heat is provided to sustain the at least partial endothermic dehydrogenation of the carrier at reaction temperature. The at least partially dehydrogenated and at least partially selectively oxidized liquid carrier is regenerated in a catalytic hydrogenation process where apart from an incidental employment of process heat, gaseous hydrogen is the primary source of reversibly contained hydrogen and the necessary reaction energy.

24 Claims, 9 Drawing Sheets

